



www.dirtcar.com

2019 Rule(s) Bulletin

Bulletin: 2019 – 01 – November 29, 2018

The following is a revision to the 2019 DIRTcar UMP Modified Rules:

Please note: this document is intended to communicate the changed portions of the complete rules effective the date indicated.

DIRTcar UMP Modifieds

TECHNICAL BULLETIN

Effective Date: November 29, 2018

DIRTcar UMP Modifieds

15.7 – Body

K. Deck height should measure within 1"-inch from side-to-side.

15.7.1 – Interior and Driver Compartment

F. Interior decks must be flat from side to side. Interior decks may have a up to a total of 6"-inches of "rake" from the most forward part of the deck to the most rearward part of the deck as described below. Interior deck from the rear of the seat forward may be flat or have up to 3"-inches of rake. The interior deck from the rear of the seat to the rear of the car cannot exceed 3"-inches of rake regardless of how much rake the front portion measures. The rake of the rear portion of the interior deck must be in a straight flat line from the rear of the seat to the rear of the car.

15.8.3 – Rear Suspension

G. Radius rods must attach to the frame brackets and to the birdcages using metal spherical rod ends or mono ball type bearings. Non- metallic bearings and or bushings will not be permitted. All mounting holes for attaching radius rods must be round and properly fit the fastener being used to prevent movement.

15.8.4 – Springs and Shocks

E. Brake and or lift bar springs must be a minimum of 5"-inches in diameter.

F. Shock and spring covers will not be permitted.

Sam Driggers

DIRTcar Racing Director

